TYAN®

High Performance Computing Platform

1U 2-way SMP System

GT24-B2932-E

B2932G24V4H-E / B2932G24W4H-E

▼ Front View

▼ Back View

2-way AMD Opteron™ platform designed for HPC virtualization applications

- Dual LGA 1207-pin sockets support up to (2) AMD 45nm Quad-Core Opteron™ 2300 series processors
- Support AMD Dual Dynamic Power Management (DDPM) feature
- nVIDIA nForce® Professional 3600 (NFP 3600)
- (16) 240-pin DDR2 DIMM slots support up to 64GB registered DDR2 667/533/400 w/ ECC memory
- (1) Full-Height/ Full-Length PCI-E x16 slot (via M2083-RS)
- (4) hot-swap 3.5" SAS HDD bays w/ RAID 0, 1, 1E support (B2932G24W4H-E)
- (4) hot-swap 3.5" SATA-II HDD bays w/ RAID 0, 1, 0+1, 5 support
- (2) GbE LAN
- (1) EPS1U 650W PSU w/ PFC
- Optional TYAN® M3291 SMDC for IPMI v2.0 support

Model #	No. of HDD supported	Backplane	Power Supply
B2932G24V4H-E	(4) Hot-swap SATA-II	4-port SAS/ SATA	650W PSU
B2932G24W4H-E	(4) Hot-swap SAS	4-port SAS/ SATA	650W PSU

(Specifications are subject to change without notice. Items pictured may only be representative.)

GT24-B2932-E

B2932G24V4H-E / B2932G24W4H-E

▼TOP View



SPECIFICATIONS

Enclosure
- TYAN GT24 industry standard 19" rack-mountable 1U chassis
  - (1) slim DVD-ROM bay
  - (4) 3.5" hot-swap HDD bays
- Dimension
  - H1.72" x W17.2" x D25.4"
  - H43.6mm x W436mm x D645mm

Processors
- Dual LGA 1207 sockets
- Support up to (2) 45nm Quad-Core AMD Opteron™ 2300 series processors
- Support 2.0GT/s HyperTransport™ link
- Support AMD Dual Dynamic Power Management (DDPM) feature

Chipset
- nVIDIA nForce® Professional 3600 (NFP 3600)
- NEC uPD720400 PCI-X Bridge
- SMSC SCH5017 Super I/O chip w/ temperature sensing

Memory
- Dual-channel memory bus
- (16) 240-pin DDR2 DIMM slots
- Support up to 64GB registered DDR2 667/533/400 w/ ECC memory

Expansion Slots
- (1) FH/FL PCI-E x16 slot (via M2083-RS)
- Total (1) expansion slot

Integrated 2D / 3D PCI Graphics
- ATI ES1000 graphic controller
- PCI interface
- 32MB DDR video frame buffer memory

Server Management
- Optional TYAN M3291 SMDC
- IPMI v2.0 compliant

BIOS
- AMI BIOS on 8Mbit LPC Flash ROM
- Support ACPI 2.0
- Serial Console Redirect
- User configurable H/W monitoring
- PXE via Ethernet, USB device boot
- PnP, DMI 2.0, WfM 2.0 Power Management

Integrated LAN Controller
- Marvell 88E1121 GbE PHY
- Total (2) RJ-45 LAN ports

Motherboard
- B2932G24V4H-E
  - TYAN® S2932G2NR-E
- B2932G24W4H-E
  - TYAN S2932WG2NR-E

Power Supply
- EPS1U high-efficiency 650W PSU w/ PFC
- 100V~240V full-range AC input

Rear Panel I/O Ports
- (1) stacked PS/2 connectors for mouse and keyboard
- (1) stacked 2-port USB 2.0
- (1) DB-9 serial port
- (1) D-sub VGA port
- (2) side-by-side RJ-45 connectors

Front Panel Features
- I/O
  - (2) USB 2.0 ports
- LED indicators
  - Power LED
  - (2) LAN LEDs
  - HDD Active LEDs
  - ID LED
  - Warning LED
- Switches
  - Power
  - Reset
  - ID
  - NMI

Storage
- B2932G24V4H-E
  - Integrated SATA-II controller in NFP 3600
  - (4) hot-swap 3.5" SATA-II HDDs w/ RAID 0, 1, 0+1, 5 support
- B2932G24W4H-E
  - Integrated LSI SAS1068E 8-port SAS controller
  - (4) hot-swap 3.5" SAS HDDs w/ RAID 0, 1, 1E support
- Pre-installed slim type DVD-ROM for both SKUs

System Cooling
- (2) 40mm x 40mm x 56mm 15,000rpm heavy-duty fans with fan speed monitor and control
- (3) 40mm x 40mm x 28mm 15,000rpm heavy-duty fans with fan speed monitor and control
- (2) Passive CPU Heatsink

Environment Temperature
- Operating temperature 5 °C ~ 35°C
- Non-operating temperature -40 °C ~70°C

Regulatory
- FCC Class B (Declaration of Conformity)
- CE (Declaration of Conformity)

MITAC INTERNATIONAL CORP.
Enterprise Business Unit

USA
Tel: +1-510-651-8868
Fax: +1-510-651-7688

Taiwan
Tel: +886-2-2652-5888
Fax: +886-2-2652-5805

Japan
Tel: +81-3-3769-8311
Fax: +81-3-3769-8328

Netherlands
Tel: +31-10-2467722
Fax: +31-10-4735881

China
Shanghai Tel: +86-021-61431188 Ext 1373
China Tel:-86-010-62381108 Ext 2043